Brickcom

5 Megapixel
Mini Box Network Camera

MB-500A Series

HDTV 1080p/720p ● WiFi/3G/4G Wireless Connection ● PoE

- Most Intelligent, Compact and Affordable 5M Camera
- HDTV Quality (Full HD 1080p @ 30fps Streaming)
- Removable IR-cut Filter Superior for Night Vision
- Intelligent Multi-Profile Sensor Management for Different Environment
- Support 802.11a/b/g/n Dual Band Wireless Connectivity
- WPS Supported for Easy Wireless Network Setup
- Support 3G/ 4G (WiMAX/LTE) Wireless Connectivity
- Edge Recording/ Micro SD slot
- PoE/ Two-way Audio/ Built-in Mic and Speaker/ DIDO/ Privacy button

Photo Indication & Dimension Diagram

1. Adjustable focal Lens
2. Light Sensor
3. Illumination LED
4. Built-in Microphone
5. Speaker
6. Privacy LED
7. WPS LED (*)
   FW Upgrade LED
8. Wireless LED (*)
   Ethernet LED
9. Power LED
10. Ethernet RJ45 Socket
11. Power Connector
12. Reset Button
13. DIDO Terminal I/O Connector
14. WPS Button (*)
15. Privacy Button
16. Micro SD/SDHC slot
17. USB Port for 3G/4G ***(MB-500Ap)***

(*) WMB-500Ap



Camera

Models	**MB-500Ap** Board Lens, USB for 3G, IR LED, PoE **WMB-500Ap** Board Lens, WiFi, IR LED
Hardware System	CPU: 533 MHz Flash: 32M RAM: 256M DDR
Image Sensor	Sensor Type : 1/2.5" CMOS Sensor Sensor Resolution : 2592x1944 pixel
Minimum Illumination	0 lux (IR ON, B/W)/ 2 lux (F1.6, Color)
IR Illuminators	Built -in IR Illuminators, effective up to 15 meters IR LED: 30pcs IR wavelength: 850nm
Lens	Lens Type: Board Lens Focal Length: f= 4 mm Iris: F1.6 View Angle: (H): 90°/ (V): 67°/ (D): 112°

Video

Video Image Compression	H.264 / MPEG4 / MJPEG
Video Setting	Audio Exposure Control: Sport/ Normal/ Night Vision/ User Defined Manual Exposure Control: 1/20000~1/5s Manual Gain Control: 1X ~ 32X Manual White Balance Control: 2000K~7000K
S/N Ratio	38.1 dB
Image Resolution	**5M :** 2592x1944 @ 10fps (5M supports MJPEG only) **4M :** 2304x1728 @ 15fps **3M :** 2048x1536 @ 18fps **2M (Full HD):** 1920x1080 @ 30fps **1M (HDTV):** 1280x720 @ 30fps

Events and Alarm Management

Events	Motion Detection/ Schedule/ Audio Detection/ Digital Input
Alarm	Stream/Snapshot to FTP/Email/Samba/SD-Card HTTP/Email Notification/ Digital Output

Audio

Audio Streaming	2-way Audio Support
Audio Compression	G.711, AMR (8 kHz, Mono, PCM)
Audio Input/ Output	Built-in MIC & Speaker

General

Communication	Ethernet : one 10/100Mbps RJ-45 Supported Protocols : TCP/IP, UDP, ICMP, DHCP, NTP, DNS, DDNS, SMTP, FTP, HTTP, Samba, PPPoE, UPnP, RTP, RTSP, RTCP, IPv6
Interface & Buttons	Built-in Microphone & Speaker Ethernet RJ45 Socket Power Connector DIDO Terminal I/O Connector Reset Button WPS Button **(WMB-500Aps)** Privacy Button Micro SD/SDHC slot USB Port for 3G/4G (**MB-500Ap)**
Day & Night Support	Mechanical ICR , triggered by sensor
Power Input	**MB-500Ap:** PoE 802.3af/ DC12V 1A **WMB-500Ap**：DC12V 1A
Max. Power Consumption	**MB-500Ap:** 6.4 watts **WMB-500Ap:** 6.8 watts
Environment	Operating Temperature 0°C ~ 50°C (32°F ~122°F), Operating Humidity : 10% ~ 80%
Dimension	163 (L) X163 (W) X 125 (H) mm
Weight	**MB-500Ap**: 470g **WMB-500Ap**: 477g
Certification	FCC, CE
Warranty	Limited 2-year warranty

	Wireless (11a/b/g/n dual band WiFi)	Wired (802.3af PoE)	USB port for 3G/ 4G(WiMAX/LTE)
MB-500A Series			
MB-500Ap		✓	✓
WMB-500Ap	✓		

Work Best With

Accessories Options

DWRT-600N
Dual Band Wireless Router

PS-588I
8-port 10/100M PoE Fast Ethernet Switch

BP-1000
UPS power pack (Edge Recording)

Copyright© 2012 Brickcom Corporation. All rights reserved. All other company names and products are trademarks or registered trademarks of their respective companies. We reserve the right to introduce modifications without notice.

Brickcom
info@brickcom.com